




Features:

- Easily fitted in seconds to most wheels.
- Highly developed lock, 10 pin drill and pick resistant with a million plus possible key combinations.
- Multi fit holes, adjustable to fit varying tyre widths.
- No keys required for locking, simple snap shut lock.
- Inner and outer arms constructed from 75 x 6mm steel with reinforcing strips on inside faces for added strength.
- Inner arm protrudes deep into rear of wheel to fit between rim and brake disc/drum.
- Plastic sleeved ends to inner and outer arms to protect wheels from damage.
- Zinc plated coating to steel components.
- Sold Secure approved.

MODEL	TYRE WIDTH	DIMENSION A	WEIGHT
* EM500SS	Min 150mm- 220mm MAX	180mm	5.6kg
EM600SS (Inc. WS5's)	Min 150mm- 220mm MAX	180mm	5.6kg
EM540SS	Min 200mm- 310mm MAX	180mm	6.4kg
EM4X4SS	Min 200mm - 310mm MAX	230mm	6.4kg
EM1000	Min 300mm- 400mm MAX	295mm	8.0kg
EM2000	Min 400mm- 500mm MAX	295mm	8.0kg

* Sold Secure approved when used in conjunction with locking wheel nuts.

Bulldog Security Products Ltd

Units 1 - 4 Stretton Road, Much Wenlock, Shropshire, TF13 6DH.

Tel: 01952 728171

sales@bulldogsecure.com www.bulldogsecure.com

Secured by Design



Police Preferred Specification

©COPYRIGHT 2003 BULLDOG SECURITY PRODUCTS LTD